

The LEXF is designed and listed for **CI D1** explosion, hazardous, marine and wet locations. This product is ideal for retrofitting High Pressure Sodium (HPS) and Metal Halide (MH) fixtures for increased energy savings and maintenance.



1 SERIES	2 SOURCE	3 VOLTAGE	4 CCT	5 OPTICS / BEAM	6 LENS
LEXF	L1: 80W L2: 100W L3: 150W	V1: 120-277VAC (50/60Hz) V2: 347-480VAC (50/60Hz)	4: 4,000K 5: 5,000K	V25: 25° V60: 60° V120: 120°	C: Clear
Note: Product comes standard with: (3) 3/4" NPT Hubs: pendent and two sides hubs, and a yoke bracket pre-installed 10Kv Surge Protector built in 3 Ft. 3-Wire whip, factory installed					

### CERTIFICATIONS

UL844 / CSA C22.2 No.137 (Hazardous)  
 CI D1, Grps C,D  
 CI D2, Grps A,B,C,D  
 CII D2, Grps F,G  
 CIII  
 Simultaneous Presence  
 Paint Spray Listed  
 T-Codes: CI D1=T6 / CI D2=T4A / CII D2=T4A  
 UL1598 (Wet/Damp)  
 UL1598A (Marine Outside)  
 DLC Premium (inquire for specific part numbers)  
 Lumen Maintenance (L70) >50,000 hrs. (reported)  
 CRI >70  
 -40°C to 60°C Ambient  
 RH Ambient Humidity 5% to 95%  
 NEMA 3 and NEMA 4X  
 IP66  
 FCC

### CONSTRUCTION

Copper-free aluminum housing and yoke  
 Tempered glass lens  
 Powder coat black  
 (3) 3/4" NPT Hubs  
 All exposed fasteners are stainless steel  
 Weight: 34 lbs.

### ELECTRICAL

120-277 / 347-480VAC  
 10Kv surge protector built in - Standard  
 3Ft. 3-Wire whip standard, factory installed

### FEATURES

High Lumen output up to 130 Lm/W  
 Shock and Vibration resistant  
 Thermal Shock and impact resistant lens  
 Mounting: Wall (Flood), Stanchion, Ceiling, and Pendent  
 Light weight compact design  
 5 Year Warranty

### PERFORMANCE

Source	Voltage (VAC) 50/60Hz	Input Current (A)	Wattage (W)	CCT	Lumens* (Lm)
L1	120-277	.67 - .29	80	4,000K	9720
	347-480	.23 - .17		5,000K	10290
L2	120-277	.83 - .36	100	4,000K	11760
	347-480	.29 - .21		5,000K	12280
L3	120-277	1.25 - .54	150	4,000K	18360
	347-480	.43 - .31		5,000K	18650
					*Nominal values



# LEXF

## EXPLOSION PROOF

Chemical Processing • Grain Processing • Metals & Mining • Oil / Gas • Water Treatment



### ACCESSORIES - (Field Installed, Order Separately)

Part Number	Description	
WG01	Wire Guard Stainless Steel 304 (not suitable for use in paint spray applications)	
SN01	Slipfitter Mount Bracket Fits 2 3/8" Outside Diameter Stanchion	

### SUGGESTED MOUNTING



Wall / Flood



Ceiling (shown with wire guard)  
(#WG01 ordered separately)



Pendant\*

\*Conduit and stanchion shown for illustration purposes only



Stanchion\*  
(#SN01 ordered separately)

### DIMENSIONS

